



Food Grade GP






Food grease

Description

High-quality grease for food and pharmaceutical industry in cases where accidental contact of the lubricant with the product is possible. It is made on the basis of white oils, which have undergone a deep water purification and integrated aluminum thickener. Contains a complex of additives that meet the special requirements of the food industry.

YUKO food Grade GP - meets the international standards for NSF International Grease oils in the H1 category and manufactured according to ISO 9001. YUKO Food Grade GP got the NSF International Certificate No. C0289383-01 dated May 17, 2016.

Enabled packing

-  Cartridge 400ml
-  Plastic pail 0,8kg
-  Plastic pail 9kg
-  Plastic pail 17kg
-  Barrel 180kg

Benefits

- Resistance to water and steam, caustic solutions, alkaline solutions, salty water;
- Wide temperature range of application;
- Excellent adhesion to metal surfaces;
- Bio-stable and does not color the surfaces. Has a neutral smell and taste;
- Compatible with seals used in food equipment;
- Does not contain natural products, animal origin or GMOs;
- Suitable for use in places where vegetarian food is cooked.

Compliance

NLGI 2 | DIN KX2P-40 | ISO L-XCCEB 2 | NSF H1 |

Typical characteristics

Thickening agent	Al-Complex
Base oil	white naphthenic
Penetration at 25°C, 0,1mm, not less than	220
Effective viscosity at -30°C	1200
Dropping point, °C, not less than	230
Colloid stability , %, not more	15
Resistance to water washing at 79°C, %	3,5
Evaporation, %, not more	5

Temperature range



Produced according to TU U 20.5-31852954-082:2016. This information is reference and it can be changed without a notice.