



YUKO TRITON WR 2

Water resistant multigrade grease based on anhydrous calcium.

Description

It is recommended for application in marine vessels mechanisms, water transport and coastal engineering in any climate; the cars chassis, heavy forest, agricultural and building machinery, mining machinery and other equipment operating under conditions of water influence, dirt, snow, even under extremely low temperatures; rolling and sliding bearings under heavy loads, low and medium speeds under the influence of dirty and salt water washout; household and small equipment (bicycles, motor blocks, saws, cutting machines) - all year round; rust preventing lubrication for equipment and metalware storage.

Enabled packing

 Tin bucket 17,0kg

Benefits

- Heavy loads wear resistance;
- Lasting protection against corrosion in salt and dirty water;
- High adhesion to metal and excellent joints sealing;
- Provides mechanisms protection at extremely low temperatures - down to -40 ° C

Compliance

NLGI 2 |

Typical characteristics

Penetration at +25° C , mm•10-1	280
Dropping point , °C	150
4 Ball test: Weld Point Test , H	1960
4 Ball test: Wear Test, mm	0,6

Temperature range



Выпускается по ТУ У 23.2-31852954-068:2014. Данная информация является справочной и может быть изменена без уведомления. Данная публикация от 16.06.2015 заменяет все ранее опубликованные описания данного продукта.