



IND VEGA SYNT 5W-40

Synthetic hydrocracking motor oil.

Description

Multigrade universal synthetic motor oil designed for petrol and diesel engines. Effectively protects and ensures engine running over a wide temperature range and in temperate climates. Recommended for engines with a standard drain intervals of both modern, and last generations.

Enabled packing

 Canister 1L

 Canister 4L

 Canister 5L

 Tin bucket 20L

 Barrel 200kg

Benefits

- Retains its operational properties for as long as possible, which allows to increase engine oil change intervals;
- Absence of high-temperature and low-temperature deposits in the engine;
- Significantly lengthens the engine life due to the content of a multifunctional complex of additives;
- Reduces fuel consumption and exhaust emissions;
- Possesses excellent low-temperature, anti-friction, anti-corrosion, detergent and antioxidant properties;
- Low volatility at high operating temperatures.

Compliance

SAE 5W-40 | API SL/CF | ACEA A3/B4 | MB 229.3 | VW 502.00/505.00 | BMW LL-01 |

Typical characteristics

Viscosity mm ² /s at 100 °C	12,5-16,3
Density at 20°C, kg/m ³	900
Viscosity Index	140
Pour point °C	-35
Flash point in open crucible, °C	200
Alkaline number, mg KOH / g	9

Temperature range



JV YUKOIL LLC, 69014, Ukraine, Zaporizhzhia, Bazova str., 3a according to TU U 19.2-31852954-116: 2021. The parameters and their values indicated in the table are typical for this product, have a reference character and are not may be a legal guarantee of the properties of the product or the suitability of the product for a particular application. The actual parameters of the product are reflected in the quality passport for each batch produced. The manufacturer reserves the right to change the product information at any time without notice. Technical support service: support@yukoil.com