



IND SP **YUKO REDUS CLP 150**

Industrial gear oil.

Description

Intended for use in domestic and imported equipment. Made by innovative technology using high quality imported additives, meets basic international standards to gear oils.

Gear Oil REDUS CLP 150 is recommended for use in industrial gears (in industrial drives, conveyors, handling devices), metals (in the steel industry in circulation lubrication systems for rolling mills drives), mines and quarries (in enclosed gears, open gears, sliding knots, ropes), high-speed drives (high-speed rotating equipment, turbines, centrifugal compressors).

Enabled packing

 Canister 20L

 Barrel 200L

 In bulk

Benefits

- High EP properties, providing long-term work of gears without tearing, welding and breakage;
- Wide temperature range of application;
- Can be used in more loaded reducers;
- A long-term drain interval;
- Reduce costs of maintenance and repair of equipment.

Compliance

ISO 150 | DIN 51517/3: CLP |

Typical characteristics

Kinematic viscosity at 40°C, mm ² /s, within	135-165
Viscosity index	90
Flash point, °C, min	210
Pour point, °C, not higher	-18
Acid index, mg KOH/g, max	1,3
Density at 20°C, kg/m ³ , max	910
Ash content, %, max	0,3
Load wear index, (LWI)	441
Scar wear diameter (196 N), max	0.45

Temperature range



Produced according to TU U 23.2-31852954-069-2014. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.