



SP **YUKO STANDART 15W-40**

All-season motor oil.

Description

All-season motor oil with synthetic components is recommended for gasoline and highly forced middle forced diesel engines without supercharging or turbo charging, cars, vans and trucks.

Enabled packing

 Tin bucket 20L

 Canister 20L

 Barrel 200L

 In bulk

Benefits

- has improved anticorrosion properties and thermal stability;
- has high anti-wear properties;
- provides the maintenance of engine parts to keep clean due to the special properties of the oil and low temperature to prevent sedimentary figure deposits;
- provides easy starting in the winter due to good compatibility of oils at low temperatures;
- compatible with mineral oils from other manufacturers at the same level of quality of API;
- has a high level of consumer demand due to the successful combination of price and quality.

Compliance

SAE 15W-40 | API SJ/CF-4 |

Typical characteristics

Kinematic viscosity at 100 °C, mm ² /s	14.5
Density at 20°C, kg/m ³	885
Viscosity index	123
Alkalinity number, mg KOH/g	6.5
Flash point in open crucible, °C	225
Temperature of hardening, °C	-27

Temperature range



Produced according to TY Y 23.2-31852954-008-2003. This information is reference and it can be changed without a notice. This article is from 01/11/2013, it replaces all the early published descriptions of the product.