



**PVL** **YUKO TRANS 80W-90**

**Universal all-season transmission oil.**

**Description**

Used in mechanical transmissions of passenger cars and trucks, differentials, transfer gears, heavy duty transmissions, and other units where oil grade API GL-4 recommended.

**Enabled packing**

 Canister 1L

 Canister 3,8L

 Canister 20L

 In bulk

**Benefits**

- High performance within wide range of operating conditions for a long time;
- Good anti-foam and anti-corrosion properties, compatible with seal materials;
- A high level of wear protection within a wide load range;
- The modern package of extreme pressure additives provides a high level of protection for various loads, including impact loads.

**Compliance**

**SAE 80W-90 | API GL-4 | ZF TE-ML 16K, 08, 02L, 01L | Volvo 97305, DAF, Iveco | MB 235.11 | MAN 341 Type E3, MAN 341 Type Z4 | Renault Axle (B0032/2 Annex3) |**

**Typical characteristics**

Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	15.0
Density at 20 °C, kg/m <sup>3</sup>	891
Viscosity index	100
Flash point in open crucible, °C	225
Pour point, °C	-25

**Temperature range**



Produced according to TU U 23.2-31852954-013-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.