



CVL TURBOSYNT DIESEL 10W-40

Semi-synthetic motor oil for diesel engines.

Description

Intended for modern air and turbo diesel engines of passenger cars, vans and trucks and other commercial vehicles.

Produced of high-quality foreign base oils with additives, providing optimum performance throughout the service life.

Enabled packing

 Canister 1L

 Canister 5L

 Tin bucket 20L

 Barrel 200L

Benefits

- Consistently high performance in various operating modes;
- Optimum lubricating properties and detergency;
- Easy cold start in winter;
- Prevents high and low temperature deposits formation in the engine;
- Reliable wear protection of engine parts throughout the service life;
- Compatible with all engine sealings;

Compliance

SAE 10W-40 | API CH-4/SL | ACEA E5, E2 | MB 228.1, MAN M271, Volvo VDS/VDS-2 |

Typical characteristics

Kinematic viscosity at 100°C, mm ² /s	14.9
Density at 20°C, kg/m ³	885
Viscosity index	134
Alkalinity, mg KOH/g	8,5
Flash point in open crucible, °C	223
Pour point, °C	-32

Temperature range



Produced according to TU U 23.2-31852954-045:2010. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.